

Puracon Stationary PRO



Puracon Stationary PRO

Puracon Stationary PRO is the professional solution for humidity monitoring during the filling procedure. The PRO version provides separated sensor and display unit. The sensor is connected directly to the high-pressure line after the humidity filter and is linked to the display unit via a data cable.

Specifications

- » Aluminum sensor housing with G1/4" inlet and outlet
- » Display unit (Ø 96 x 37 mm) for wall mounting with sensor cable (length: 2 m)
- » Power supply cable (length: 1.7 m) with CE plug 100 - 230 V ~ 50/60Hz
- » Digital LCD display with humidity display in mg/m³ and error warnings
- » Higher accuracy by new temperature and pressure compensation
- » 2 monitoring LEDs, adjustable limits
- » 2 output signals (24V)
- » Sensor cables with 5, 10, 15 or 30 m available for surcharge
- » Approved up to 350 bar

Available versions

- » 420 bar sensor (stainless steel)
- » 12 V DC
- » 24 V DC
- » Ex with ATEX certification



Technical Data

| Technical Data | Puracon Stationary PRO |
|-----------------------|-------------------------------------|
| Operating pressure | 150 - 350 bar / optional 420 bar |
| Power supply | 100 - 240 V / optional 12V or 24VDC |
| Connector | Sensor: G1/4 thread |
| Protection rating | IP64 |
| Operating temperature | +5°C to +45°C |

Lenhardt & Wagner GmbH

An der Tuchbleiche 39
68623 Hüttenfeld/Germany

Phone: +49 (0)62 56 - 8 58 80 -0
Fax: +49 (0)62 56 - 8 58 80 -14

eMail: service@lw-compressors.com
Internet: www.lw-compressors.com